



Ideal for

- SOHO
- K-12
- First Responders
- Remote Monitoring

(MM) Magnetic Mount

Paddle Solution



Features

- 698 - 2700 MHz
- 2X2 MIMO LTE
- Omni Directional
- Magnetic Mount



Product Description

Parsec's MM is a compact high performance two in one MIMO LTE based magnetic mount M2M antenna. This rugged omni-directional antenna works on all the common worldwide LTE bands with high efficiency.

Patent pending.



LTE Frequency Ranges

698 - 960 MHz

1710 - 2700 MHz

Mechanical

Dimensions (Base)	5.5in x 2.5in x 0.5in
Dimensions (Antennas)	6.5in x 0.9in x 0.3in
RF Cable Length	Choice of 1, 2, or 6 foot cables

Environmental

Operating Temperature	-40°C to 85°C
Ingress Protection	IP54 Outdoor

Ordering

Standard Antenna Part Numbers

Configurations	Part Number	Description
2:1	PTAMM2LTE003	2 LTE, 3ft cable
	PTAMM2LTE006	2 LTE, 6ft cable
	PTAMM2LTE010	2 LTE, 10ft cable
	PTAMM2LTE015	2 LTE, 15ft cable

Notes:

N type connector is recommended for outdoor usage due to it being waterproof. N type is also best used for cable runs longer than 25ft due to it being a stronger connection.

SMA connectors have a max torque of 3-5 inch lbs.



Parsec Technologies
972-804-4600
support@parsec-t.com